

# DECLARATION OF PERFORMANCE

According with Regulation (EU) №305/2011



## TERAZID GT-11

**№ 20150316-01-D**

1. Unique identification code of product type:

**TERAZID GT-11**

2. Type, batch or serial number or other element allowing identification of the construction product as required under Article 11, paragraph 4 of Regulation (EU) №305/2011:

**Liquid waterproofing  
/batch number printed on the package/**

3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Ready-to-work one-component waterproofing.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer, as required under Article 11, paragraph 5 of Regulation (EU) №305/2011:

**TERAZID Ltd.  
5 „5004” Str., Gara Iskar, Sofia 1528, Bulgaria  
tel. +35929799971  
e-mail: office@terazid.com**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12, paragraph 2 of Regulation (EU) №305/2011:

**Not applicable.**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Regulation (EU) №305/2011 for construction products, Annex V:

**System 4**

7. In case of the declaration of performance concerning a construction product for which it was issued European Technical Assessment:

**EN 14891 - Liquid-applied water impermeable products for use beneath ceramic tiling bonded with adhesives – Requirements, test methods, evaluation of conformity, classification and designation**

# DECLARATION OF PERFORMANCE

According with Regulation (EU) №305/2011



## TERAZID GT-11

### 8. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Adhesion with the concrete base	1,18 N/mm <sup>2</sup>	EN 1015-12
Waterproofing under pressure - 150 kPa	waterproof	EN 14891
Consistency	3000 m.Pa.s	EN ISO 2555
Density	1.6 g/cm <sup>3</sup>	EN 2811-1
Relative prolongation	120 %	EN 12311-2
Bond strength after water immersion	0.96 N/mm <sup>2</sup>	EN 14891
Bond strength after freeze-thaw cycles	0.61 N/mm <sup>2</sup>	EN 14891
Content of non-volatile compounds	75.23 %	EN 3251:2008

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Sofia**  
**23.01.2023**

**Rosen Stankov:**  
General Manager  
TERAZID Ltd

