## WOOD DECOR



ADHESIVES • PLASTERS • THERMAL INSULATION

## № 20150828-D

1. Unique identification code of product type:

## WOOD DECOR

2. Type, batch or serial number or other element allowing identification of the construction product as required under Article 11, paragraph 4 of Regulation (EU) №305/2011:

#### Decorative finishing plaster with wooden effect /batch number printed on the package/

3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

# White cement-based mixture for making fine protective and decorative coatings resembling wood facings.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer, as required under Article 11, paragraph 4 of Regulation (EU) №305/2011:

#### TERAZID Ltd. 5 "5004" Str., Gara Iskar, Sofia 1528, Bulgaria tel. +35929799971 e-mail: office@terazid.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12, paragraph 2 of Regulation (EU) №305/2011:

#### Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Regulation (EU) №305/2011 for construction products, Annex V:

#### System 4

7. In case of the declaration of performance concerning a construction product covered by harmonized standard:

BDS EN 998-1 - Specification for mortar for masonry - Part 1: Rendering and plastering mortar.



## **DECLARATION OF PERFORMANCE**

According with Regulation (EU) №305/2011

# WOOD DECOR



ADHESIVES • PLASTERS • THERMAL INSULATION

8. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class A1	BDS EN 13820
Bulk density	$1500 \text{ kg/m}^3$	BDS EN 1015-10
Compressive strength	$3.5 \text{ N/mm}^2$	BDS EN 1015-11
Bond strength	$1.9 \text{ N/mm}^2$	BDS EN 1015-12
Flexural strength	$1.9 \text{ N/mm}^2$	BDS EN 1015-11
Coefficient of capillary absorption	$0.09 \text{ kg/m}^2.\text{min}^{0.5}$	BDS EN 1015-18
of water - c	class W <sub>2</sub>	
Coefficient of heat transmission	0.57 W/m.K	BDS EN 1745
- λ <sub>10,dry</sub>		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sofia 06.01.2020



