DECLARATION OF PERFORMANCE According with Regulation (EU) №305/2011



ADHESIVES • PLASTERS • THERMAL INSULATION

NIVELOR MAXI TOP

№ 20130709-55-D

1. Unique identification code of product type:

NIVELOR MAXI TOP

2. Type, batch or serial number or other element allowing identification of the construction product as required under Article 11, paragraph 4 of Regulation (EU) №305/2011:

Calcium-sulphate self-leveling screed /batch number printed on the package/

3. Intended use or uses of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Self-leveling mixture for floor unevenness from 2 to 20 mm, for interior application.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer, as required under Article 11, paragraph 4 of Regulation (EU) №305/2011:

TERAZID Ltd. 5 "5004" Str., Gara Iskar, Sofia 1528, Bulgaria tel. +35929799971 e-mail: office@terazid.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12, paragraph 2 of Regulation (EU) №305/2011:

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Regulation (EU) №305/2011 for construction products, Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by harmonized standard:

BDS EN 13813 - Screed material and floor screeds - Screed material - Properties and requirements.



DECLARATION OF PERFORMANCE

According with Regulation (EU) №305/2011

NIVELOR MAXI TOP



ADHESIVES • PLASTERS • THERMAL INSULATION

8. Declared pert	formance
------------------	----------

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class A1	BDS EN 13820
Compressive strength	26.8 N/mm^2	BDS EN 13892-2
	Class C25	
Bond strength	3.3 N/mm^2	BDS EN 13892-8
	Class B2.0	
Flexural strength	7.0 N/mm^2	BDS EN 13892-2
	Class F7	
Abrasion resistance	$35,6 \text{ cm}^3/50 \text{ cm}^2$	BDS EN 13892-3
(Böhme method)	Class A22	
Coefficient of capillary absorption	$0.29 \text{ kg/m}^2.\text{h}^{0.5}$	BDS EN 1062-3
of water - c		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sofia 06.01.2020



