

INSTRUCTION FOR APPLICATION

CONTENTS:

MICRO CEM GROUT 30 - dry mixture in a plastic bag (10 kg)

- binding resin in a bucket (2.8 kg)

PURPOSE: A two-component product, part of the high-tech system **MICRO CEM**, designed for wall, floor and ceiling decoration. The **GROUT 30** is the first of the three layers in the series and it is used as basis of the system.

APPLICATION: The application of GROUT 30 starts with priming of the base surface. In case of non-water absorbing surfaces, such as stone, faience or terracotta, the base should be primed with high-strength flexible primer TOP GRIP. In case of water absorbing surfaces, such as cement screeds or plasters, the base should be prepared with deeply penetrating primer PRIME DB-

MICRO CEM GROUT 30 should be applied after the complete drying of the primer.

Preparing the mixture should start by gradually adding the dry component to the liquid component, in ratio 10 kg: 2.8 kg (dry: liquid), and mixing with a mechanical stirrer until a homogeneous mass is achieved. The fresh mixture should stand for about 5 minutes and then must be stirred again before the application begins.

GROUT 30 is applied in one layer in combination with alkali resistant fiberglass mesh (145-160 g/m²), due to achieve optimal strength results. The prepared mixture should be applied within 1 hour.

NOTES:

Recommended work temperature +5°C to 25°C.

Do not mix with other materials.

Do not apply under direct sunlight or strong air flows.

CONSUMPTION: One package of **MICRO CEM GROUT 30** (10 + 2.8 kg) is sufficient to cover around 8 -10 m², depending of the thickness of applying. Observe the components mixing proportions when working on areas smaller than 8 m².

STORAGE: 12 months into the originally sealed packages, in a dry and ventilated place, without the danger of freezing and direct sunlight. It is recommended to be stored on pallets.

MICRO CEM GROUT 30

Dry component (10 kg)



Does not contain soluble Cr (VI) into a quantity greater than 0,0002 % within the period of storage.

Hazard statements: (H-codes)

H315 - Causes skin irritation.

H318 – Causes serious eye damage.

H335 – May cause respiratory irritation.

Danger!

Precautionary statements: (P-codes)

P101 – If medical advice is needed, have product container or label at hand.

P102 – Keep out of reach of children.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P315 - IF IN EYES: Rinse cautiously with water for several

minutes. Get immediate medical advice/attention.

Liquid component (2.8 kg)

Precautionary statements: (P-codes)

P101 – If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P262 – Do not get in eyes, on skin, or on clothing.

P280 – Wear protective gloves/protective clothing/eye protection/face

P301 + P311 - IF SWALLOWED: Call a POISON CENTER/doctor.

P305 + P351 + P313 - IF IN EYES: Rinse cautiously with water for several minutes. Get medical advice/attention.